

Electric Series Scissor Lifts

0407SE(1330SE)

Compliance with ISO/CE/ANSI/CSA/AS/CU-TR/KCS standards

Product Highlights

- Platform capacity up to 240kg(529lbs)
- Easily passes through standard doors and can access elevators
- Exclusive open chassis reduces daily maintenance time
- DC motor drive, giving a longer runtime

Standard features		
■ Maintenance-free battery	■ Automatic braking system	■ Full-stroke operation
■ Proportional control	■ Emergency lowering system	■ Forklift pocket and lifting eyes
■ Bumper rail	■ Emergency stop at both platform and ground controls	■ Electrophoresic paint technology
■ 4×2 drive	■ Fault diagnosis system	■ Foldable guardrail
■ Non-marking tyres	■ Tilt protection	■ Overload sensing system
■ Integrated hand shield	■ Automatic pothole guard	
Optional features		
■ Overhead anti-collision device	■ Headlight	■ RCBO
■ AC power to platform		

SINOBOOM

Sinoboom Intelligent Equipment Co Ltd

大東機械貿易有限公司
Galaxy Machinery Trading Co. Ltd



Address : LOT2219RP&2226, DD129 Deep Bay Road, Lau Fau Shan, N.T., HK
Tel : 852-2472 4777 Fax : 852-2472 6667
Website : <http://www.galaxymt.com> E-mail : galaxymachineryhk@gmail.com

Electric Series Scissor Lifts

0407SE(1330SE)

Compliance with ISO/CE/ANSI/CSA/AS/CU-TR/KCS standards

SINOBOOM



Model		0407SE(1330SE)
Dimension		
Max Working Height		5.8m(19')
A	Max Platform Height	3.8m(12'6")
B	Max Horizontal Extension	0.6m(23.6")
C	Length-Stowed	1.42m(4'8")
D	Width-Stowed	0.76m(2'6")
Height - stowed	Rail Folded	1.67m(6'5")
	E Rail Unfolded	1.97m(6'6")
	Fixed Rail	1.97m(6'6")
F	Wheelbase	1.11m(3'8")
Ground Clearance(Pothole Guard Stowed)		0.065m(2.5")
Ground Clearance(Pothole Guard Deployed)		0.02m(0.75")
Platform Dimensions(L×W×H)		1.34m×0.7m×1.1m(4'4"×2'3"×3'6")
Performance		
Platform Allowable Occupants(Indoor)		2 persons
Platform capacity		240kg(529lbs)
Lift Extension Capacity		100kg(220lbs)
Drive Speed-Stowed		4km/h(2.5mph)
Drive Speed-Raised		0.8km/h(0.5mph)
Lift Time(Unloaded)		30s~33s
Descent Time(Unloaded)		25s~30s
Gradeability		25%
Turning Radius(Inside/Outside)		0.3m/1.35m(12"/4'5")
Tilt Rating(Front to Back/Side to Side)		3°/1.5°
Tyre Size/Type		230×80mm (9×3")80/solid
Power		
Batteries		12V×2/115Ah
Power Source		24V DC
Drive Mode		Motor, Rear wheel
Charger Input		100~240V AC
Charger Output		15A
Hydraulic System Capacity		5L(1.1gal)
Weight		
Weight(Indoor)		880kg(1,940lbs)
Standards Compliance		ISO/CE/ANSI/CSA/AS/CU-TR

